

**Product range: "consumer ready"**

**Sunpack - power at hand whenever you go !  
outdoor & camping**



The Sunpack is your **ideal companion for all outdoor activities** such as camping, trekking, mountain climbing .. all activities where mobility is the key!

It is a **lightweight, compact and rollable** solar charger for portable electronic devices like mobile and satellite phones, PDA's, GPS's, MP3 players, digital cameras through their standard car chargers.

It is **easily transportable** and gives you power at hand wherever you go.

**Easy plug & play** via the universal cigarette lighter adapter.

**Specifications**

Reference	Dimensions cm x cm	Weight kg	Nominal Voltage V	Operating Current mA	Power Output W
Sunpack 7W	rolled: 35.0 x ø6.5 unrolled: 35.0 x 90.0	0.70	12	450	6.75
Sunpack 14W	rolled: 35.0 x ø8.0 unrolled: 35.0 x 150.0	1.10	12	900	13.5

**Product range: "consumer ready"**

**Sunslick - extend the life of your battery!  
marine & yachting**



Perfect for battery maintenance and charging, the Sunslick flexible solar battery charger has been specifically designed expressly for **marine and yachting applications**.

The Sunslick modules can be mounted on curved surfaces such as hatch covers, boat decks and vehicle roofs.

They can also be tied down on sail covers, dinghies or caravan awnings.

Sunslick modules are **waterproof** and **lightweight**.

**Specifications**

Reference	Dimensions cm x cm	Weight kg	Nominal Voltage V	Operating Current mA	Power Output W
Sunslick 7W	35.0 x 69.5	0.48	12	450	6.75
Sunslick 14W	35.0 x 130.5	0.90	12	900	13.5
Sunslick 27W	64.2 x 130.5	1.50	12	1800	27.0

September 2006

## 12 volt semi rigid solar panels

### Why select Sunware

- Semi rigid construction is perfect for mounting on slightly curved surfaces.
- Tough, non slip surface may be stepped on.
- Ideal for mounting on surfaces which get hot.
- Shadow tolerance means less power loss.
- Stainless steel backing for strength.
- Extra cells give better response.
- Strong corner eyelets\* for easy fixing.



\* except slimline (5mm thick) panels

### Panel Specifications

	Watts Peak power	Amps Peak power	mm A x B	mm Thick	kg Weight
<b>12 Volt panels</b>					
AR SP SW 18/1	18.0	1.1	475 x 465	9	3.0
AR SP SW 27/1	27.0	1.4	640 x 465	9	3.2
AR SP SW 35/1	35.0	2.0	770 x 495	9	4.5
AR SP SW 35/1 SRM	34.0	2.0	770 x 495	9	4.4
AR SP SW 35 K-L	35.0	2.0	740 x 440	5	4.5
AR SP SW 35 K-R	35.0	2.0	740 x 440	5	4.5
AR SP SW 54/1	54.0	3.0	910 x 625	9	6.7
AR SP SW 54 K-L	52.5	3.0	850 x 560	5	6.5
AR SP SW 54 K-R	52.5	3.0	850 x 560	5	6.5
AR SP SW 3066	70.0	3.6	891 x 638	5	6.1
<b>24 Volt panels</b>					
AR SP SW 35/1 24v	35.0	1.0	770 x 495	9	4.5
AR SP SW 54/1 24v	54.0	1.5	910 x 625	9	6.7

*All modules have 39 or 40 cells, 3m of cable and a 3 year warranty*

## Regulators

### Sealed solar regulators.

SR PV7D 12	SES	PV7D 12V Flexcharge Regulator 7 Amp (dual battery)
SR PV7D 24	SES	PV7D 24V Flexcharge Regulator 7 Amp (dual battery)
SR SG 04	Morning Star	SG4 12V Sunguard Regulator 4 Amp
SR SS 06	Morning Star	SS6 12V Sunsaver Regulator 6 Amp
SR SS 10	Morning Star	SS10 12V Sunsaver Regulator 10 Amp
SR SS 11	Morning Star	SS11 24V Sunsaver Regulator 10 Amp
SR SS 20	Morning Star	SS20 12V Sunsaver Regulator 20 Amp



### Phocos unsealed solar regulators

SR CML 10	Phocos	CML10 12/24V Solar Regulator 10 Amp
SR CML 15	Phocos	CML15 12/24V Solar Regulator 15 Amp
SR CR 10LC	Phocos	CR10LC 12/24V Solar Regulator 10 Amp (bargraph)
SR CR 20LC	Phocos	CR20LC 12/24V Solar Regulator 20 Amp (bargraph)
SR CR 30W	Phocos	CR30W 12/24V Charge Divert 30 Amp
SR PL 20	Phocos	PL20 12/24/48V Solar Regulator 20 Amp (multifunction programmable)



## Regulators / Monitors

SR FX 150	SunWare	Fox 150: 12v, 16 Amp, Volts/Amps Display, surface mount
SR FX 150/E	SunWare	Fox 150E: 12v, 16 Amp, Volts/Amps Display, flush mount
SR FX 250	SunWare	Fox 250: 12v, 16 Amp, Volts/Amps + Functions Display, surface mount
SR FX 250/E	SunWare	Fox 250E: 12v, 16 Amp, Volts/Amps + Functions Display, flush mount
SR FX 350	SunWare	Fox 350: 12v, 16 Amp, Volts/Amps + Functions Display for twin battery, surface mount
SR FX 350/E	SunWare	Fox 350E: 12v, 16 Amp, Volts/Amps + Functions Display for twin battery, flush mount
SR SPCC 10E	Sollatek	Sollatek 12/24v, 10 Amp Day Switch/Timer

